

CNG CYLINDER VALVES VM05 AUTOMATIC



CNG CYLINDER AUTOMATIC VALVE VM05

CNG automatic cylinder valves VM05 are homologated in accordance with the European Regulations ECE R110, approved in accordance with ENARGAS and in compliance with ISO15500 standards.

Our VM05 valves are provided with manual tap, excess flow valve, solenoid valve and separated safety devices (thermofuse T-PRD and burst disc). They are also supplied with rubber protection for cylinder thread.

Important: these valves do not need the gas-tight housing.

VM05 Vented Automatic accessories:

VM4524 VM05 vented valve locking wrench

VM1023 Fitting accessories bag Ø6 mm

VM1025 Fitting and cap bag Ø6 mm

SKU: N/A

PRODUCT DESCRIPTION

CNG CYLINDER VENTED AUTOMATIC VALVE	STANDARD
Material	Hot forged brass, CNC machined
Weight	1.18 kg
Product type	Automatic vented CNG cylinder valve
Max. working pressure	260 bar
T-PRD activation temperature	+ 110° C ± 10° C
Burst pressure (T20° C)	340 bar ± 10%
Manual tap opening/closing angle	900° (270° upon request)
Pipe connection	M12x1 pipe Ø 6 mm
Tank thread	DIN (25E), upon request BS, NGT
Coil voltage	12 V DC (upon request 24V)
Coil power	15 W
Coil connection	AMP Minitimer or AMP Superseal

[DOWNLOAD CATALOGS](#)