

Page 1 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

(GB)

Thread sealant 50 ml Art.: 243445

1.2 Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses of the substance or mixture:
Adhesive
Sector of use [SU]:
SU 1 - Agriculture, forestry, fishery
SU19 - Building and construction work
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]: PC 1 - Adhesives, sealants Process category [PROC]: PROC 8a - Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities Article Categories [AC]: AC99 - Not required. Environmental Release Category [ERC]: ERC99 - Not required. Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet ®

Albert Berner Deutschland GmbH, Bernerstrasse 4, 74653 Künzelsau, Germany Phone: +49 79 40 12 10, Fax: +49 79 40 12 13 00 info@berner.de, www.berner.de

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.



Page 2 of 15

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (BRC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) 1272/2008 (CLP) The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

Not applicable

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006. The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

REGULATION (EC) No 648/2004

n.a.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Registration number (REACH)	
Index	-
EINECS, ELINCS, NLP	-
CAS	-
content %	
Classification according to Regulation (EC)	
1272/2008 (CLP)	

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16. The substances named in this section are given with their actual, appropriate classification! For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.



Page 3 of 15

(GB)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445

SECTION 4: First aid measures

4.1 Description of first aid measures

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Unsuitable cleaning product:

Solvent

Thinners

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Irritation of the eyes

Skin irritation possible with prolonged contact.

4.3 Indication of any immediate medical attention and special treatment needed $_{\text{n.c.}}$

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon Oxides of nitrogen

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective respirator with independent air supply. According to size of fire

Full protection, if necessary



Page 4 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445

Cool container at risk with water. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin. If applicable, caution - risk of slipping

6.2 Environmental precautions

If leakage occurs, dam up.

(GB)

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1. 7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed. 7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing.

Not to be stored in gangways or stair wells.

Protect from direct sunlight and warming.

Store cool

Store in a dry place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters



Page 5 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445

Chemical Name	Silica, amorph	nous			Content %:
WEL-TWA: 6 mg/m3 (tota	al inh. dust),	WEL-STEL:			
2,4 mg/m3 (resp. dust)					
Monitoring procedures:	-				
BMGV:			Other information	I:	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

Silica, amorphous						
Area of application	Exposure route / Environmental compartment	Effect on health	Descrip tor	Value	Unit	Note
Workers / employees	Human - inhalation	Long term, local effects	DNEL	4	mg/m3	

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

8.2.2 Individual protection measures, such as personal protective equipment General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374) Minimum layer thickness in mm:

0,4

(GB)

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.



Page 6 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445

Protective hand cream recommended.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments)

Respiratory protection: Normally not necessary.

Thermal hazards: Not applicable

(GB)

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Yellow
Odour:	Mild
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	> 100 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	1,05 g/cm3 (25°C)
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Not miscible
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	No
Decomposition temperature:	Not determined
Viscosity:	18000 - 30000 mPas (Brookfield (6/20))



Page 7 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445

Explosive properties: Oxidising properties: 9.2 Other information Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content:

(GB)

Product is not explosive. Not determined

Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity
The product has not been tested.
10.2 Chemical stability
Stable with proper storage and handling.
10.3 Possibility of hazardous reactions
No dangerous reactions are known.
10.4 Conditions to avoid
See also section 7.
Protect from direct sunlight and warming.
10.5 Incompatible materials
See also section 7.
Metal salts
10.6 Hazardous decomposition products
See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

Possibly more information Thread sealant 50 ml					lioutionji	
Art.: 243445						
Toxicity/effect	Endp oint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.



Page 8 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445

œ

Specific target organ	n.d.a.
toxicity - single	
exposure (STOT-SE):	
Specific target organ	n.d.a.
toxicity - repeated	
exposure (STOT-RE):	
Aspiration hazard:	n.d.a.
Symptoms:	n.d.a.
Other information:	Classification
	according to
	calculation
	procedure.

Silica, amorphous						
Toxicity/effect	Endp oint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC0	0,139	mg/l/ 4h	Rat		References
Skin corrosion/irritation:				Rabbit		Not irritant, References
Serious eye damage/irritation:				Rabbit		Not irritant, Mechanical irritation possible., References
Respiratory or skin sensitisation:				Guinea pig		Not sensitizising
Symptoms:						eyes, reddened

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Thread sealant 5	0 ml						
Art.: 243445		-					
Toxicity/effect	Endpoi	Time	Valu	Unit	Organism	Test	Notes
	nt		е			method	
Toxicity to fish:							n.d.a.
Toxicity to							n.d.a.
daphnia:							
Toxicity to algae:							n.d.a.
Persistence and							n.d.a.
degradability:							
Bioaccumulative							n.d.a.
potential:							
Mobility in soil:							n.d.a.
Results of PBT							n.d.a.
and vPvB							
assessment							



Page 9 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445

Other adverse	n.d.a.
effects:	
Other information:	According to the
	recipe, contains no
	AOX.
Other information:	DOC-elimination
	degree(complexing
	organic
	substance)>=
	80%/28d: n.a.
Water solubility:	Insoluble

Silica, amorphous	S						
Toxicity/effect	Endpoi nt	Time	Valu e	Unit	Organism	Test method	Notes
Toxicity to fish:	LC50	96h	>100 00	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
Toxicity to daphnia:	EC50	24h	>100 00	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisati on Test)	
Persistence and degradability:							Abiotically degradable.
Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

(GB)

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.



Page	10	of	15
Page	10	0I	10

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445

SECTION 14: Transport informatio

General statements		
UN number:	n.a.	
Transport by road/by rail (ADR/RID)	n.u.	
UN proper shipping name:	D 0	
Transport hazard class(es):	n.a.	
Packing group:	n.a.	
Classification code:	n.a.	
LQ (ADR 2015):	n.a.	
Environmental hazards:	Not applicable	
Tunnel restriction code:		
Transport by sea (IMDG-code)		
UN proper shipping name:		
Transport hazard class(es):	n.a.	
Packing group:	n.a.	
Marine Pollutant:	n.a	
Environmental hazards:	Not applicable	
Transport by air (IATA)		
UN proper shipping name:		
Transport hazard class(es):	n.a.	
Packing group:	n.a.	
Environmental hazards:	Not applicable	
Special precautions for user		
Unless specified otherwise, general measures for safe transport must be followed.		
entees speaned ethermise, general medeal es for sure transport must be followed.		

Transport in bulk according to Annex II of MARPOL and the IBC Code Non-dangerous material according to Transport Regulations.

SECTION 15:	Regulatory	information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National rules/regulation for the compliance with maximum quantities with regard to phosphates and or phosphorous compounds must be observed and complied with.

For classification and labelling see Section 2.

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

n.a.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP): Not applicable



_@				
Page 11 of 15				
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445				
The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).				
Albert Berner Deutschland GmbH Bernerstrasse 4 D - 74653 Künzelsau Tel +49 79 40 12 10 Fax +49 79 40 12 13 00 info@berner.de www.berner.de	Berner Gesellschaft m.b.H. Industriezeile 36 A - 5280 Braunau / Inn Tel +43 77 22 800 508 Fax +43 77 22 800 184 berner@berner.co.at www.berner.co.at	Berner Belgien NV/SA Bernerstraat 1 B - 3620 Lanaken Tel +31 45 533 93 133(8.00h- 16.00h) Tel +31 6 290 27 464 (16.00h- 8.00h) Fax +31 455 33 92 43 info@berner.be www.berner.be		
Montagetechnik Berner AG Kägenstraße 8 CH - 4153 Reinach / Bl. 1 Tel +41 61 71 59 222 Fax +41 61 71 59 333 berner-ag@berner-ag.ch www.berner-ag.ch	Berner A/S Stenholm 2 DK - 9400 Nørresundby Tel +45 99 36 15 00 Fax +45 98 19 24 14 info@berner.dk www.berner.dk	Berner Montaje y Fijación, S.L. P.I. "La Rosa VI" C/Albert Berner, 2 E - 18330 Chauchina-Granada- España Tel +34 90 21 03 504 Fax +34 90 21 13 190 berner-spain@berner.es www.berner.es		
Berner Kft. Táblás u. 34 H - 1097 Budapest Tel +36 (1) 347 1059 Fax +36 (1) 347 1045 info@berner.hu www.berner.hu	Frimann-Berner AS Holmaveien 25 N - 1339 Vøyenenga Tel +47 66 76 55 80 Fax +47 66 76 55 81 info@berner.no www.berner.no	Berner Succ. Luxembourg 105, Rue des Bruyères L - 1274 Howald Tel +31 45 533 93 133 (8.00h- 16.00h) Tel +31 6 290 27 464 (16.00h- 8.00h) Fax +31 455 33 92 43 info@berner.lu www.berner.lu		
Berner spol. s r.o. Jinonická 80 CZ - 158 00 Praha 5 Tel +420 225 390 666 Fax +420 225 390 660 berner@berner.cz www.berner.cz	Berner,S.A. Av. Amália Rodrigues,3510 Manique de Baixo P - 2785-738 Săo Domingos de Rana Tel ++351 21 448 90 60 Fax ++351 21 448 90 69 marketing.pt@berner.pt www.berner.pt	Berner Polska Sp. Z.o.o. Al. Gen. T. Bora-Komorowskiego 25a PL - 31-476 Kraków Tel +48 12 297 62 40 Fax +48 12 297 62 02 office@berner.pl www.berner.pl		



Page 12 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445

Albert Berner UAB Kalvarijø 29B, LT09313, Vilnius, Lithuania Tel +370-52104355 Fax +370-52350020 info@berner.lt

(GB)

Berner Pultti Oy Volttikatu 6 FI - 70700 Kuopio Tel +358-207-590 220 Fax +358-207-590 221 kuopio@berner-pultti.com www.berner-pultti.com

Berner Endüstriyel Ürünler Sanayi ve Ticaret A.Ţ. Ferhatpaţa Mah. G 7 Sok. 31/2 TR - 34858 Kartal-Samandýra / ÝSTANBUL Tel +90 (0) 216-4713077 Fax +90 (0) 216-4719625 info@berner.com.tr www.berner.com.tr

Berner Produkten b.v. Vogelzankweg 175 NL - 6374 AC Landgraaf +31 45 53 39 133 (8.00h-16.00h) +31 6 290 27 464 (16.00h-8.00h) info@berner.nl www.berner.nl Berner SK Berner s r.o. Jesenského 1 SK - 962 12 Detva Tel (+421) 45 5410 245 Fax (+421) 45 5410 255 berner@berner.sk www.berner.sk

Mitras d.o.o Brdnikova ulica 34e SL-1000 Ljubljana Tel +386-1-256-62-46 Fax +386-1-256-62-45 mitras@siol.com

Berner S.p.A. Via dell 'Elettronica 15 I - 37139 Verona Tel +39 04 58 67 01 11 Fax +39 04 58 67 01 34 info@berner.it www.berner.it

Berner s.a.r.l. ZI Les Manteaux F - 89331 Saint-Julien-du-Sault Cedex Tel +33 38 69 94 400 Fax +33 38 69 94 444 contact@berner.fr www.berner.fr Albert Berner Montageteknik AB Elektravägen 53 S - 126 30 Hägersten Tel +46 85 78 77 800 Fax +46 85 78 77 805 info@berner.se www.berner.se

BERNER d.o.o CPM Savěca Śanci Trgovaćka 2 HR - 10000 Zagreb Tel +38512 499 470 Fax +38512 499 480 e-mail: safetydata-hr@berner.co.at

Albert Berner srl Str. Vrancei Nr. 51 - 55 RO - 310315 Arad Tel +40 257 212291 Fax +40 257 250460 office@berner-romania.ro www.berner-romania.ro

Albert Berner SIA Liliju 20, Marupe, Mārupes novads, LV-2167, Latvija Tel +37167840007 Fax +371678440008 info@berner.lv

(c) COPYRIGHT 1987 - 2050 ALL RIGHTS RESERVED

Any abbreviations and acronyms used in this document:

ACArticle Categoriesacc., acc. toaccording, according toACGIHAmerican Conference of Governmental Industrial HygienistsADRAccord européen relatif au transport international des marchandises Dangereuses par Route (=European Agreement concerning the International Carriage of Dangerous Goods by Road)AOELAcceptable Operator Exposure LevelAOXAdsorbable organic halogen compoundsapprox.approximately



(GB) Page 13 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445 Art., Art. no. Article number Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP) ATE BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany) BCF **Bioconcentration factor** BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation) BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol) BMGV Biological monitoring guidance value (EH40, UK) BOD Biochemical oxygen demand BSEF Bromine Science and Environmental Forum bw body weight CAS **Chemical Abstracts Service** CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids CESIOComité Européen des Agents de Surface et de leurs Intermédiaires Organiques **CIPAC Collaborative International Pesticides Analytical Council** Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling CLP and packaging of substances and mixtures) CMR carcinogenic, mutagenic, reproductive toxic COD Chemical oxygen demand CTFA Cosmetic, Toiletry, and Fragrance Association DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon DT50 Dwell Time - 50% reduction of start concentration DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes) dw dry weight for example (abbreviation of Latin 'exempli gratia'), for instance e.q. EC European Community ECHA European Chemicals Agency European Economic Area EEA EEC European Economic Community European Inventory of Existing Commercial Chemical Substances EINECS ELINCS European List of Notified Chemical Substances ΕN **European Norms** FPA United States Environmental Protection Agency (United States of America) ERC Environmental Release Categories ES Exposure scenario etc. et cetera EU **European Union** EWC European Waste Catalogue Fax. Fax number gen. general GHS Globally Harmonized System of Classification and Labelling of Chemicals GWP Global warming potential Hen's Egg Test - Chorionallantoic Membrane HET-CAM HGWP Halocarbon Global Warming Potential IARC International Agency for Research on Cancer IATA International Air Transport Association



Page 14 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445 Intermediate Bulk Container IBC International Bulk Chemical (Code) IBC (Code) Inhibitory concentration IC IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive IUCLID International Uniform ChemicaL Information Database LC lethal concentration LC50 lethal concentration 50 percent kill LCLo lowest published lethal concentration Lethal Dose of a chemical 1 D LD50 Lethal Dose, 50% kill LDLo Lethal Dose Low LOAELLowest Observed Adverse Effect Level LOEC Lowest Observed Effect Concentration LOEL Lowest Observed Effect Level LQ Limited Quantities MARPOL International Convention for the Prevention of Marine Pollution from Ships n.a. not applicable n.av. not available n.c. not checked n.d.a. no data available NIOSH National Institute of Occupational Safety and Health (United States of America) NOAEC No Observed Adverse Effective Concentration NOAFI No Observed Adverse Effect Level NOEC No Observed Effect Concentration NOEL No Observed Effect Level ODP Ozone Depletion Potential OECD Organisation for Economic Co-operation and Development org. organic PAH polycyclic aromatic hydrocarbon PBT persistent, bioaccumulative and toxic PC Chemical product category PF Polyethylene PNEC Predicted No Effect Concentration POCP Photochemical ozone creation potential ppm parts per million **PROC** Process category PTFE Polytetrafluorethylene RFACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals) 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. REACH-IT List-No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT. RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail) SADT Self-Accelerating Decomposition Temperature SAR Structure Activity Relationship SU Sector of use SVHC Substances of Very High Concern Tel. Telephone ThOD Theoretical oxygen demand TOC Total organic carbon

(GB)



Page 15 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revised on / Version: 10.06.2015 / 0002 Replaces revision of / Version: 21.05.2015 / 0001 Valid from: 10.06.2015 PDF print date: 11.06.2015 Thread sealant 50 ml Art.: 243445

œ

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure
limit (15-minute reference period) (EH40, UK).
WHO World Health Organization
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.